

ROMANZA

thickness: 1.2-1.4MM
average size: 53 sq. ft
availability: In Stock
category: Semi-Aniline
finish type: Antique
raw material: European
Made in Italy

Romanza is semi aniline, hand antiqued leather which provides any piece with a sophisticated yet oh so comfortable look. Romanza has been hand stained with a combination of subtle oils and waxes, followed by a protective topcoat to give it excellent wear ability. It is then hot ironed to give it an added finish and a see through look reminiscent of the old English Bridle leathers. Once upholstered, the beauty and workmanship of this leather is amplified and brought to life.

Colorways available: Black, Caramel, Chivas, Chocolate, Cinnamon, Citron, Deep Sea, Gunmetal, Harness Brown, Midnight, Oak, Peacock, Sage, Sand, Smoke, Spice, Walnut and Whiskey

SPECIFICATIONS

performance characteristics

PERFORMANCE LEATHER

| | |
|---|---|
| EN ISO 4045 DETERMINE Ph & Ph (DIFFERENCE FIGURE) | Min 3,2 |
| ISO105/B02 | |
| COLOR FASTNESS OF LEATHER TO LIGHT: XENON LAMP | Grey Scale ≥ 3 on specimen Grey Scale = 3 on Reference Blue Wool #4 |
| EN ISO 15700 COLOR FASTNESS TO WATER SPOTTING | Grey Scale ≥ 3 (No permanent swelling) |
| ISO 11641 COLOR FASTNESS OF LEATHER TO PERSPIRATION | 80 Cycles ≥ 3.5 |
| EN ISO 11640 COLOR FASTNESS OF LEATHER TO RUBBING | 500 Cycles Dry ≥ 4 250 Cycles Wet ≥ 3.5 |
| EN ISO 11644 FINISH ADHESION | 3 N/cm |
| EN ISO 3376 | Tensile Strength ≥ 8 Mpa % Elongation $\leq 80\%$ |
| MEASURE TENSILE STRENGTH AND % ELONGATION | |
| EN ISO 5402 FLEXING ENDURANCE (FLEXOMETER METHOD) | 50,000 Cycles (no finish damage cracks) |
| EN ISO 17233 COLD CRACK RESISTANCE OF FINISH | -15°C (no finish cracks) |
| EN ISO 3377-1 TEAR STRENGTH (SINGLE EDGE TEAR) | >20 N Minimum |
| flame resistance | |
| CA TB 117 - 2013 | Complies |
| NFPA - 260 CIGARETTE IGNITION | Class 1 |
| FMVSS 302 | Complies |

